

# Installation instructions



---

## 1. Use:

---

*For applications where the GR panel cannot be hung on the wall (e.g. in the case of glass surfaces).*

---

## 2. Contents of the set:

---

- 2 × chromium support (base diameter 130mm)
- 4 × plastic cover for the GR panel brackets
- 1 × mains plug (to be installed on the supply lead if the panel is to be used as a portable heater)
- 2 × adjustment screw



# FENIX

---

### *3. Method of installation:*

---

*The supports are intended only for use with the GR type and only ~~vertical~~ horizontal installation (insertion of the longer side of the panel into the supports)!*

*The GR panel is to be inserted into the slits in the supports; the supports are subsequently attached to the panel using the adjustment screws. The distance between the supports and the side edge of the panel shouldn't exceed 100mm for the GR 300, 500 panel and 150mm for the GR 700, 900 panel. The panel when placed in the supports cannot be moved by sliding across the floor – the panel can slide out from its supports and be damaged.*

*The distance of the bottom edge of the panel from the floor is 55mm.*

*Plastic covers are to be placed onto the panel brackets. The panel is stable on the supports; the maximum allowed deflection from the axis is 15°.*

*For permanent installation, we recommend attaching the supports to the floor using screws – there are two openings with a diameter of 6mm in the base for screws with countersunk heads (these screws aren't included in the package).*

*If the mains plug is installed, there is no restriction on how the poles may be placed.*

---

### *4. Maintenance:*

---

*The chromium supports may be cleaned using preparations which do not contain solid particles (abrasives).*

